

Die new generation JUMBO and JUMBO combiline



97+286.02.1009


PÖTTINGER

After 10 successful years of JUMBO high performance 20% performance increase highest operating efficiency

Your benefits at a glance

Powerful one-man unit designed for tractors up to 331 kW / 450 HP

- New drive transmission secured with 2500 Nm
- New drawbar with a 3.3 and 4.4 sh to / 3.0 and 4.0 t static vertical load
- New forced-steering axle
- New 8-row pickup
- New beater rotor drive transmission secured with 500 Nm
- New beater rotors

Operating efficiency combined with maximum convenience

- Adjustable automatic loading system ensures optimised filling of trailer
- Ergonomic working thanks to laterally pivoting knife bank (Easy Move)
- Innovative control terminals for convenient operation from the cab

Top harvesting quality for long-term success

- Appropriate chop length provides optimum forage structure for the rumen
- Fully automatic individual knife protection and mounting for uniform chopping quality
- Fully automatic „autocut“ blade sharpening device on option
- Clean pickup of forage

Customised solutions for different needs

- Product range with 15 different JUMBO and JUMBO combine models, for tractor powers from 160 to 450 HP



New 8-row pickup

- The new 8-row pickup with a larger diameter and optimized speed guarantees a 20% higher capacity from all JUMBO and JUMBO combine models.
- The collection area from the pickup tines to the rotor has also been optimised and adapted to the rotor capacity.
- Well tested pendular pickup with 6.56' / 2.00 m working width.
- Long-term lubrication and low-maintenance tine mounting channel make overall maintenance easier.

Key features of the new JUMBO silage trailers from Pöttinger are a new pickup, new loading rotor and increased productivity. Now the capacity of exceptionally powerful tractors (up to 450 hp) can be put to full effect with this silage trailer generation.

With this cost-effective technique the forage harvester can deliver high quality grass silage. Also, a particularly important aspect is that the stones in the forage are not split into fragments, which can help to avoid causing any injuries to bovine digestive tracts.

Performance silage trailers efficiency



New beater rotor unloading system

- Discharge overload protection increased to 1500 Nm for 20% higher unloading performance
- Beater drive shaft is fitted with freewheel – quieter start-up
- Extra strong driveshaft
- New beater shape (twist design) delivers higher performance, third beater rotor on option

The beater rotor drive transmission is protected and on the right-hand side of the trailer. Two sturdy angular gear units and a chain transmit the power to the beater rotors. The drive shaft is secured with a cam clutch coupling with 1500 Nm.



JUMBO 10010 combine



The ultimate flagship

An innovation in the extensive silage trailer fleet is the JUMBO combine 10010 with a capacity of 3531 cu ft / 100 m³ (1670 cu ft / 47.3 m³ DIN volume), making it useable both as a silage trailer as well as a harvest trailer. The result is maximum versatility and increased machine operating efficiency. In addition to its high level of operating efficiency, the Pöttinger JUMBO combine is extremely cost-effective and once again affirms the significance of self-loading wagon systems as the way ahead.

JUMBO combine 10010 L

Volume to DIN	1670 cu ft / 47,3 m ³
Pickup width	6.56' / 2.00 m
Knives	45
Chop length	1.34" / 34 mm
Length	39.34' / 11.99 m
Width	9.22' / 2.81m
Height	12.37' / 3.77 m
Weight	25975 lbs / 11780 kg

All information is provided without obligation



New drawbar

- Vertical load 3.3 or 4 shto 3 or 4 t
- New optimised shape
- Tighter turning angle thanks to narrower design to 60° depending on tractor (with or without active steering system)
- Support leg further in, lock pins shifted inwards in transport position – no risk of collision with tyres

JUMBO	JUMBO combine
3.3 shto / 3 t on option	3.3 shto / 3 t standard
4.4 shto / 4 t on option	4.4 shto / 4 t on option



Alois Pöttinger
 Maschinenfabrik GmbH
 Industriegelände 1
 A-4710 Grieskirchen
 Telefon +43 (0) 7248/600-0
 Telefax +43 (0) 7248/600-2513

Importer for UK:
 LandMec Pottinger
 Cantrell Works
 Bittaford, Ivybridge
 Devon PL21 0EZ
 England
 Phone: 01752 891285
 info@landmecpottinger.co.uk
 www.landmecpottinger.co.uk

www.poettinger.at

Importer for Ireland:
 T. Traynor & Sons Ltd.
 Cashel Road, Clonmel
 Co. Tipperary
 Ireland
 Phone: 052/25 766
 info@traynor.ie
 www.traynor.ie

Sales & Service for Canada:
 Poettinger Canada Inc.
 650, Route 112
 St-Cesaire, J0L 1 T0, PQ
 CANADA
 Tel.: (450) 469-5594
 sales.canada@poettinger.ca
 Sales & Service for the US:
 Poettinger Canada Inc.
 650, Route 112
 St.-Cesaire, J0L 1 T0, PQ
 CANADA
 Tel.: (450) 469-5594
 Cell: (450) 578-4081
 sales.us@poettinger.ca

Poettinger Australia P/L
 15 Fordson Road
 Campbellfield, VIC 3061
 Australia
 Phone: +61 3 9359 2969
 0407 100 453
 PottingerAust@aol.com
 www.poettinger.at

Importer for New Zealand:
 Origin Agroup
 PO Box 673, 57 Hautapu Road
 Cambridge
 Phone: 064 7 823 7582
 info@originagroup.co.nz
 www.originagroup.co.nz

