

Pöttinger NOVACAT V10

Largest mounted
mower combination



97+281.02.1007



PÖTTINGER



NOVACAT V10

As demands increase, Pöttinger sets new standards:

Flexible working width: Unrivalled on slopes, when cornering and for mowing large areas ...

The Pöttinger NOVACAT mower combinations have already made a name for themselves on the market for their operating efficiency and reliability. Now Pöttinger has raised the performance bar even further: the new NOVACAT V10 high-capacity mower is setting new standards and is the only mower combination in its class that can be mounted on a three-point linkage.

Extremely high operating efficiency

- Optimisation of mowing width by means of variable overlap

Optimum flexibility for every operation

- Unrivalled on slopes, when cornering and for mowing large areas
- Perfect ground hugging thanks to their central mounting

Excellent adaptability

- Two linkage positions for 3 m or 3.50 m / 9.84 or 11.48 feet front-mounted mowers

Reliable operation

Undiluted flexibility and operating efficiency



The special feature is the **working width optimisation** which permits flexible adaptation to different front-mounted mowers and to the different operating conditions on slopes, when cornering and when mowing large areas on the level. The difference from conventional mower combinations where the working width is fixed: these offer only a limited capability for overlap with the front-mounted mower. When cornering sharply, therefore, strips can be left unmown.

The hydraulic lateral displacement system integrated in the extending arms permits optimisation of the working width. The mower units can therefore each be offset by $\pm 7.87'' / 200 \text{ mm}$ so that there is an overlap with the front-mounted mower of $7.874 - 23.62'' / 200 - 600 \text{ mm}$. Furthermore, the two linkage positions permit a combination with 9.84 or $11.48 / 3 \text{ m}$ or 3.50 m feet front-mounted mowers. Depending on the operating conditions, therefore, the maximum working width can always be used, which greatly increases the implement's operating efficiency.

Hydraulic floating system

The best-possible ground adaptation to protect the sward is the Pöttinger's quality benchmark and this is achieved in the NOVACAT V10 mower combination via a **hydraulic floating system**. This means that the ground pressure can be adjusted quickly and easily.



In conjunction with a NOVACAT Alpha-Motion front disc mower, this results in a combination with perfect ground adaptation. "Floating cut" even on undulating ground – guaranteed soil protection and superior forage quality.

**Outstanding ease of operation:
POWER CONTROL easy-to-use
control panel**

ISOBUS-compatible as standard
Setting of the overlap between the
front mower and the mower
combination.

Easy offsetting of both mowers to right
or left when operating across the slope.
Perfect adjustment of the hydraulic floating system
for different operating conditions Headland
management, individual raising of the mower units
and an area meter are also included.



Hydraulically folding end guards as standard

A transport height of 13.09' / 3.99 m is thus achieved
without leaving the cab.



Drive via special triple-telescopic
drive shafts

NOVACAT	V10	V10 ED
Working width	28.74' – 31.36' / 8.76 – 9.56 m	
with 3.50 m / 11.5' front-mounted mower	30.12' – 32.74' / 9.18 – 9.98 m	
Number of discs	2 x 8	
Transport width	9.81' (11.32') / 2.99 m (3.45 m)	
Transport height	13.09' / 3.99 m	
Weight	5071 lbs / 2300 kg	5997 lbs / 2720 kg
Power requirement	99 kW / 130 HP	110 kW / 150 HP
<i>Alle Daten unverbindlich</i>		



Alois Pöttinger
Maschinenfabrik GmbH
4710 Grieskirchen
Industriegelände 1
Telefon 07248 / 600-0
Telefax 07248 / 600-513
landtechnik@poettinger.at
www.poettinger.at

Importer for **UK:**
LandMec Pottinger
Cantrell Works
Bittaford, Ivybridge
Devon PL21 0EZ
England
Phone: 01752 891285
Fax: 01752 891392
info@landmecpottinger.co.uk
www.landmecpottinger.co.uk

Importer for **Ireland:**
T. Traynor & Sons Ltd.
Cashel Road, Clonmel
Co. Tipperary
Ireland
Phone: 052/25 766
Fax: 052/25 802
info@traynor.ie
www.traynor.ie

Sales & Service for **Canada**
POETTINGER CANADA INC.
650, Route 112
St.-Cesaire, J0L 1T0, PQ
CANADA
Tel.: (450) 469-5594
Fax: (450) 469-4466
sales.canada@poettinger.ca

Sales & Service for the **US**
POETTINGER CANADA INC.
650, Route 112
St.-Cesaire, J0L 1T0, PQ
CANADA
Tel.: (450) 469-5594
Fax: (450) 469-4466
Cell: (450) 578-4081
sales.us@poettinger.ca

Australian office
82 Rutherford Road
Viewbank 3084 Australia
Phone: 0400 587 507
0407 100 453
Fax: 0394551878
PottingerAust@aol.com
www.poettinger.at

Importer for **New Zealand:**
Origin Agrup
PO Box 673, 57 Hautapu Road
Cambridge
Phone: 064 7 823 7582
Fax: 064 7 823 7583
info@originagroup.co.nz
www.originagroup.co.nz